



Directional Microphone, Fully Flexible 40 cm



Description

The removable, fully flexible gooseneck microphone is equipped with a *screw lock connector* for easy connection to the different delegate and interpreter units.

Its unidirectional response results in *optimal performance* even in environments with a lot of ambient noise. The gooseneck design also allows for maximum *freedom of movement*. It allows bending in all directions, over the entire 40 cm length.

Another important advantage is the *very low susceptibility to interference from mobile phones*.

Finally, the D-MIC 40 FF microphone delivers a *rich, natural sound*. It enables longer and more

comfortable meetings where participants experience less strain produced by traditional artificial and mechanical microphone sounds.

The light ring is **dark** (opaque) when the microphone is switched off, it lights up **red** when active, and **green** when in request.

Specifications

Mechanical	
Material	Brass
Color	Matt black, RAL 9011
Size (mm)	480 (w) × 25 (h) × 25 (d)
Size packed (mm)	510 (w) × 50 (h) × 45 (d)
Weight (g)	100
Weight packed (g)	160
Electrical	
Transducer principle	Back electret (condenser)
Operating principle	Pressure gradient
Polar pattern	Unidirectional, cardioid
Nominal conditions	Bias resistor = 1k2 Vdd = 3.3 V DC 1 Pa = 94 dB SPL
Max SPL @ 1 kHz	110 dB SPL (1% THD+N)
Signal to noise ratio	> 67 dB(A)
Free field sensitivity	(-40.5±2) dBV @ 1Pa, 1KHz
Power supply	3.3 V DC, 0.5 mA
Consumption	0.5 mA (without LED ring) Max 25 mA (with LED ring)
Connection	Screw lock

All information copyright **Televic Conference**, 2016. Version 1.1, April 2016

—
Leo Bekaertlaan 1 · 8870 Izegem · Belgium
Tel. +32 51 30 30 45
Fax +32 51 31 06 70

E-mail: conference@televic.com

Web: <http://www.televic-conference.com>

Televic reserves the right to change this document without notice.